

SELECTION GUIDE

CHANGEOVER SWITCHES

APPLICATIONS



COMO C
25 to 100 A



SIRCOVER M⁽¹⁾
changeover switches
16 to 80 A



SIRCO VM1
changeover switches
63 to 125 A



SIRCOVER
125 to 3200 A

Changeover between two supplies	•	•	•	•
Switching between two loads	•	•	•	•
Reversing direction of operation	•	•	•	•
BY-PASS	•			
Breaking and earthing	•	•	•	•
Enclosed switches			•	•

CHARACTERISTICS

OPERATION				
Manual	•	•	•	•
Motorised				
Automatic				
DIRECT HANDLE				
Front operation	•	•	•	•
Door mounted	•			
DOOR INTERLOCKED EXTERNAL HANDLE				
Front operation	•	•	•	•
BREAKING				
Fully visible	•	•	•	•
Visible			•	
SWITCHING				
Without overlapping contacts	•	•	•	•
Overlapping contacts	•	•	•	•
MOUNTING				
Flush mounting	•	•	•	•
Back plate mounting	•	•	•	•

(1) **SIRCOVER M** is composed of two 3 pole **SIRCO M** switches, conversion kit and a fourth pole module, if request.
(2) On request.

PAGES

see page
A.82

see page
A.8

see page
A.88

see page
A.94

